

LTD2304SE-SL 4 Channel High Performance DVR (SE-SL Series)

Features

- Real-Time High Resolution Recording
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 2 Year Warranty & Free Life-Time Technical Support



Specifications

System	Compression Format	H.264
	OS	Embedded Linux
	Input	4CH, BNC (1.0Vp-p, 75Ω)
Video	VGA Output	1*VGA:1280x1024, 800x600, 1024x768
	BNC	1*BNC Mainout
	Loop Output	NO
	Spot Output	NO
	HDMI	-
Audio	Audio Input	2CH
	Audio Output	1CH
	Bidirectional Talk	YES
Recording	Real Time Recording	NO
	D1	30(NTSC)/225(PAL)fps
	CIF	120(NTSC)/100(PAL)fps
	Recording Mode	Schedule, Manual, Motion Detection
Playback	Playback Channel	4CH
	Search Mode	Time, Event, File Management
Backup	USB Disk	1 USB2.0 port for portable HDD
	DVD Burner	-
	Backup Format	DAT or AVI
Dual Steam	Master Stream	30(NTSC)/25(PAL)fps CIF per Ch
	Network Stream	1/2 fps CIF per Ch
Remote Application	Browser	IE (windows XP/vista/7), Safari(Mac OS), Chrome, Firefox
	CMS	YES
	Mobile Phone OS	SuperCam/pro/HD for iPhone(iPad/iPad2)/Blackberry/Android
	User Access	10 users online with professional authority management
Alarm	Alarm Input	-
	Alarm Output	-
Storage	HDD (Each max. size 2 TB)	1x SATA
	e-SATA	NO
	Max HDD after Deploying	-
	DVD Writable Driver	-
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP, VISCA, SAMSUNG, RM110,HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
	Remote Control	-
Others	Power Supply	DC12V
	Operating Temperature	0°C ~50°C
	Humidity	10% ~ 90% Humidity
	Dimension	11.75"(L)×10"(W)×2.25"(H)

Front/Back View



LTD2308SE-SL 8 Channel High Performance DVR (SE-SL Series)

Features

- Real-Time High Resolution Recording
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 2 Year Warranty & Free Life-Time Technical Support



Specifications

System	Compression Format	H.264
	OS	Embedded Linux
	Input	8CH, BNC (1.0Vp-p, 75Ω)
Video	VGA Output	1*VGA:1280x1024, 800x600, 1024x768
	BNC	1*BNC Mainout
	Loop Output	NO
	Spot Output	NO
	HDMI	-
Audio	Audio Input	2CH
	Audio Output	1CH
	Bidirectional Talk	YES
Recording	Real Time Recording	NO
	D1	30(NTSC)/225(PAL)fps
	CIF	240(NTSC)/200(PAL)fps
	Recording Mode	Schedule, Manual, Motion Detection
Playback	Playback Channel	8CH
	Search Mode	Time, Event, File Management
Backup	USB Disk	1 USB2.0 port for portable HDD
	DVD Burner	-
	Backup Format	DAT or AVI
Dual Steam	Master Stream	30(NTSC)/25(PAL)fps CIF per Ch
	Network Stream	1/2 fps CIF per Ch
Remote Application	Browser	IE (windows XP/vista/7), Safari(Mac OS), Chrome, Firefox
	CMS	YES
	Mobile Phone OS	SuperCam/pro/HD for iPhone(iPad/iPad2)/Blackberry/Android
	User Access	10 users online with professional authority management
Alarm	Alarm Input	-
	Alarm Output	-
Storage	HDD (Each max. size 2 TB)	1x SATA
	e-SATA	NO
	Max HDD after Deploying	-
	DVD Writable Driver	-
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP, VISCA, SAMSUNG, RM110,HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
	Remote Control	-
Others	Power Supply	DC12V
	Operating Temperature	0°C ~50°C
	Humidity	10% ~ 90% Humidity
	Dimension	11.75"(L)×10"(W)×2.25"(H)

Front/Back View

